Cross-Domain Transferability of Learned Decision Heuristics in High-Variability Production Networks

Liam Martinez, Manufacturing Intelligence Consultant, IndustriX Dynamics, Germany, liam.martinez@industrixdynamics.com

Logan Clark, Embedded Systems Designer, IndustriX Dynamics, Germany, logan.clark@industrixdynamics.com

IndustriX Dynamics

JIGBP

Journal of Innovation in Governance and Business Practices

Volume 2, 2025

JIGBP is a peer-reviewed industry journal by IndustriX Dynamics, featuring real-world innovations in governance and business.

JIGBP accepts articles only from industrialists and scientists.

Website: https://jigbp.com

Email for submissions: submit@jigbp.com.

Received: May 2, 2025

Revised: September 5, 2025

Accepted: January 3, 2026

Abstract

Production networks which require quick internal automation and flexibility because of constantly changing workloads or participation of multiple jurisdictions and business areas require a reasoned system of solving decisions problems. Recent progress in machine learning and optimization provide effective domain-specific problem solving heuristics however, domain indifferent industrial environments warrant their use. This paper presents a new approach for assessing and enabling the transfer of learned decision heuristics across domains in heterogeneous production networks. The proposed system combines domain embedding, meta-learning, and adaptive reinforcement tuning to enable the automated application of heuristic decision policies developed for one production environment to different domains without full retraining.

Simulations in different industrial scenarios that included both discrete assembly and continuous processes show that the approach can achieve up to 88% of the target performance in the adapted domains and provides over 40% decrease in adaptation effort. Results showed that drift aware retuning improves convergence time and stability in the presence of high variability. These results confirm the possibility of cross-domain heuristic transfer and mark an advancement in the development of models for universal production intelligence of Industry 5.0.

Keywords: Cross-Domain Learning, Production Decision Heuristics, Transferability, High-Variability Manufacturing, Meta-Learning in Industrial AI.

1. Introduction

1.1 Background on High-Variability Production Environments

The evolution of manufacturing technology and smart industrial technologies, coupled with sophistication in the production systems has made the production environment more complex, integrated, and volatile especially in the recent years. A wide range of economic activities such as automobile production, electronics assembly, aerospace parts fabrication, food and beverage processing, and drug manufacturing is done in high-variability production networks [1]. These industries have to routinely manage volatility in terms of demand, frequent changes in product design, heterogeneity in the supply chain, and evolving process capabilities [2]. Globalization and competition, together with the rising requirements of customers with regards to market sensitivity and personalization to varying needs has greatly changed the situation where decision making in diverse production environments has become a core issue in operations research, Industrial Artificial Intelligence (AI), and cyber-physicals systems [3].

The shift towards the adoption of smart manufacturing has created a greater challenge for decision-making applications with reliable performance under structural uncertainty, resource uncertainty, and variable constraints [4]. Changes in environment caused by so many influences makes it extremely difficult to cope for many production planning and control models since many such models work on the basis of static environments with predetermined routing logic, schedule of tasks, and plans of decisions [5]. Most of these parameters are fixed in so many modern factories and production platforms, which is contrary to the findings on data across various industries. Different sectors have a wide variety range in important performance measures like assortment of products, uncertainty in lead time, availability of machines, and order customization from clients [6].

To highlight the degree of variability met across various production domains, the table below shows the results from a study examining operational characteristics across five selected industrial sectors. These sectors represent a wide range of discrete, continuous, and hybrid production systems, and are chosen due to their variability, task complexity, and dependence on real-time and historical data precision.

The data indicates that there are major differences in system variability within the same goal-setting industry. Take for example electronics fabrication which has the highest number of product

Table 1: Variability Characteristics Across Production Domains.

Production Domain	Product Variants	Lead Time Variability (%)	Machine Downtime Rate (%)	Average Order Customization (%)
Automotive Assembly	120	22	4.2	60
Pharmaceutical Manufacturing	15	35	2.8	80
Electronics Fabrication	340	18	3.5	40
Food Processing	45	30	5.0	75
Aerospace Components	80	25	4.0	55

variants. Its lead times are more stable in comparison to the temporal and demand driven variability encountered in pharmaceutical and food processing sectors. This heterogeneity of contexts not only makes it difficult for decision optimization within individual domains, but also makes it considerably challenging to share or transfer learned decision models across diverse production environments.

1.2 Limitations of Domain-Specific Decision Models

Manufacturing solutions for industrial purposes today tend to make use of optimization and rule-based techniques that have, to a degree, been customized for a specific production area. Within and expert, system, RL or data model environment setting, these methods operate optimally, but when applied to newer domains that possess different constraint sets, their performance diminishes considerably. The fragility stems from two limitations: overfitting to domain-specific data distributions or structural assumptions and lack of abstraction in policy design that would support generalization [7].

For instance, a scheduling algorithm that is tailored towards operations in automobile assembly lines where tasks and strokes are taken in a queue and buffer sizes have predetermined expected values is not going to be efficient in electronics manufacturing environments where processing times are stochastic and machine failures propagates nonlinearly through the network [8]. In the same manner, an inventory control policy that was learned in simulation in a pharmaceutical plant that was configured as a capital stock plant is not going to work in a highly customisable make to order aerospace component manufacturing plant. Resultant misalignments trigger increased total time to complete a task, inefficient resource use, excessive redoing of work, and in extreme cases, systemic bottlenecks or failing to comply with service agreements [9].

Irrespective of these perils, most industrial and investigative endeavours remain concentrated on seeking to enhance the in-domain accuracy of decision-making models by ways of manual or automated optimization, retraining, or fine-tuning. This approach works well under bounding conditions, but it becomes economically unfeasible in the case where many plants have to be brought under control, or when the support decision systems have to be used in organizations with a diverse set of operational activities. Also, models that are tailored to specific domains tend to be highly brittle in non-stationary environments with new product families, which is increasingly frequent in digitally interconnected and globally dispersed production networks.

The widening gap between the detail offered by standard models and the broad features needed to talk meaningfully about their implementation suggests a shift to decision making cross domain strategies that allow abstraction from deeper underlying structures yet exhibit sensitivity towards the structural diversity that exists among the various production systems.

1.3 Need for Transferable Heuristics in Smart Manufacturing

The cross-domain transferability of decision-making has evolved in some areas like natural language processing, computer vision, and robotic control because of the existence and benefits of transfer learning. These domains have greatly benefitted from a reduction in training times and an increase in generalization to novel tasks [10]. In contrast, the integration of such approaches in industrial decision-making systems has not been as successful because of the complexities and challenges posed by production systems such as tightly coupled constraints, mixed discrete-continuous variables, real-time requirements, and non-standardized domain feature representations [11].

With the integration of sensors, edge computing, artificial intelligence, and cyber-physical systems, smart manufacturing offers a useful platform for overcoming these barriers. Learning-based models that break the restrictions of fixed-rule logic can be designed thanks to the massive amounts of data provided by IoT systems and modular process structures. In this case, heuristics are policies, learned patterns, or templates of strategies that can be transferred from a source domain to a new target domain with minimum training or change in configuration needed to accomplish the new tasks [12].

Such heuristics might encompass rule abstractions such as bottleneck first scheduling learned prioritization policies incorporating deep Q networks for dispatching, or even hybrid approaches blending symbolic reasoning with machine learning. The intention is not simply code or parameter set reuse, but rather, acquiring decision relevant knowledge that is contextually agnostic such as the dependence on workload imbalance, resource contention, or job arrival pattern variability.

The implementation of transferable heuristics could yield considerable returns in the form of lower expert dependence, domain deployment speed across new sites or product lines, lower development cycles for decision systems, and boosted resilience to unexpected variability. In addition, it helps create meta-learning frameworks capable of supervising fleets of agents that operate in individual domains while enabling the sharing and refining of common decision principles through shared knowledge bases or federated learning systems from a system engineering perspective.

The issue here is in turning this concept into practice, which means formulating the architecture, algorithms, and evaluation strategies that would evaluate and optimize the transferability of acquired heuristics in complex, noisy, high dimensional production contexts, the enforceability of which is very difficult.

1.4 Research Objectives and Contributions

This work tries to meet the challenge by creating and empirically testing a new framework aimed at assessing and augmenting the cross-domain transferability of decisional heuristics in high

variability production networks. The primary working assumption is the possibility of creating adaptable, abstraction based decision policies that systematically differentiate between a variety of industrial environments and do not require extensive re-training or detailed re-configuration.

To evaluate this hypothesis, the researcher has set primary goals. First, to construct a taxonomy of production domain variability, which attempts to capture both structural and statistical differences relevant to heuristic performance, such as domain and the influence it has on domain heuristics. Second, to implement a learning architecture that allows abstraction of decision heuristics from a domain and use them in a different domain using meta-learning and domain embedding approaches. Third, to construct a simulation based experimental setup which can replicate real world production systems and measure cross domain heuristic transfer using performance metrics such as throughput, makespan, drift re-adaptation cost, and stability during variability disassembly. Fourth, to quantitatively and qualitatively evaluate transfer effectiveness across different source-target domain pairs and identify failure and success transfer conditions.

This work has primary contributions as follows:

- New conceptual and mathematical framework of analyzing heuristic transferability across industrial domains.
- A domain-agnostic meta-learner which abstracts and tunes decision heuristics using reinforcement feedback in a target environment.
- Benchmark simulation suite of multiple real world production networks with a high structural variability.
- Validation results demonstrating that the proposed framework retains 88 percent of source-domain performance in target domains and decreases adaptation overhead by more than 40 percent.
- A comprehensive analysis of the domain similarity, abstraction granularity, and adaptation mechanisms components for heuristic generalization.

Filling a significant gap within AI applied in industry and production analytics processes is the scope of this investigation which aims to execute an automated cross-domain intelligent decision making systems in the context of smart manufacturing. The research shifts the focus from accomplishing a task to a more broad and ambitious goal of ensuring automatic system functionality in diverse contexts, which aims towards the direction of Industry 5.0, where intelligent systems are expected to function in integrated human socionic, superdisciplinary, flexible production ecosystems.

2. Literature Review

2.1 Decision Heuristics in Production Planning and Control

From a business perspective, production planning and control, PPC, is concerned with the strategic and operational domain of a firm's value chain and its supporting primary activities. The increasing complex of production networks has initiated a paradigm shift among researchers and practitioners

from rigid rule based systems towards adaptive decision heuristics that encompasses many objectives, such as optimizing throughput, resource use, inventory, and lead time [13]. A heuristic is a mental shortcut that helps with problem solving by simplifying the process, which can save time and resources, particularly in situations where achieving optimal results are impossible due to limited time and resources.

In the past, heuristics for production control have been created manually by professionals who utilized prior industry knowledge and logic. For instance, dispatching orders such as shortest processing time (SPT), earliest due date (EDD), or critical ratio (CR) are, and likely will continue to be, very popular in manufacturing execution systems that aid in floor shop control [14]. The rules are normally crafted based on rules regarding product flow, machine availability, and order fulfillment, but are severely limited in use within more uncertain or variable settings. Such heuristics work less effectively under higher product variety, dynamic job arrival, or multi-site resource allocation complications [15].

As AI and data driven approaches gain popularity, many researchers have started incorporating decision process within learning models, for example – embedding them in reinforcement learning (AR) or supervised machine learning (ML) frameworks. These methods allow for the automatic scribing of heuristics through learning from past records or assimilated interactions within the production system. To elaborate more, in reinforcement learning (RL), an agent differentiates among multiple actions based on their cumulative reward and adopts a policy that constitutes deterministic or near optimal decision heuristic which is contextual to the environment conditions. So as with supervized ML where the model is supplied by expert decisions and learns to create a generalizable heuristics within the training domain.

The most recent developments in hybrid heuristics prove the effectiveness of using human intuition and machine learning in tandem. For example, the use of deep reinforcement learning (DRL) in job-shop scheduling and inventory control enables systems to exceed the cost and throughput efficiency of static heuristics. Unfortunately, there is still a glaring problem: Nearly all heuristic learning paradigms are built and tested in very small scoped areas. Their applicability to other unfamiliar or fundamentally different domains is mostly unknown, which renders them fragile and expensive to implement across heterogeneous and dynamically reconfigurable modern production networks.

2.2 Cross-Domain Learning and Transfer in Industrial AI

Cross-domain learning is the ability of a trained model to a perform a task in a different domain (the target) with little to no retraining or adaptation. This is particularly critical in industrial AI due to the wide range of operational contexts and the infeasibility of creating a specific model for each factory, production line, or market configuration. Transfer learning, one of the primary methods of cross-domain learning, has been successful in many fields of AI but is still lacking in regard to the production decision-making processes [16].

Attention has recently shifted towards the application of transfer learning to industrial quality prediction, anomaly detection, and machine condition monitoring. These applications usually have some form of feature-based or model-based transfer. In feature-based transfer, models that are

trained in more specific sets are used to extract domain-invariant features which can then be utilized in other models. On the other hand, model-based transfer reuses parameters or architectures of models that have been used before, but requires that these models are fine-tuned on a small subset of the target domain data [17].

These techniques have succeeded to a reasonable extent in environments rich in sensors, such as for predictive maintenance. However, environments with a high degree of interactivity like decision-making for scheduling, dispatching, and inventory control tend to perform rather poorly. This can be attributed to the nature of the decisions made in such problems, which depend a lot on context, constraint propagation, and hidden dynamics of processes. In addition, most known techniques for transfer assume a very high degree of similarity between the areas of transfer. This assumption holds true in theory, but in production ecosystems, it is very hard to realize.

To solve these issues, researchers have started looking into something called meta-learning, which is essentially "learning to learn." In meta-learning, the objective is to build models that can learn useful knowledge from a collection of tasks or domains. In meta-learning models, this might mean learning generalized policies or strategy templates which can be adapted to new domain instances with minimal data or feedback. This paradigm is likely to be useful for many engineering problems where each production unit contains some common structural motifs but has distinct local constraints, process flows, or demand variability.

The effectiveness of these methods of transfer is compared in the table below, which summarizes the different approaches in relation to their ease of adaptation, their scalability, their training time, and their dependency on other domains.

Reinforcement learning through meta-learning and domain adaptation has the greatest potential for generalization in decision-making tasks. These methodologies can retain significant adaptability to changes in both the source and target domains' structures or operational constraints. This flexibility, however, comes at a cost; careful modeling of certain aspects like domain proximity, reward constructs, and adaptation strategies must be implemented, which are too often mal-defined or poorly evaluated in industrial research.

Table 2: Comparison of Transfer Learning Methods in Industrial Decision Systems.

Method	Adaptability to New Domain	Training Time in Target Domain	Dependency on Domain Similarity	Scalability Across Domains	Industrial Applications
Supervised Fine-Tuning	Moderate	High	High	Low	Predictive Quality Modeling
Feature-Based Transfer	Low to Moderate	Medium	Very High	Low	Sensor Calibration
Case-Based Reasoning	Moderate	Low	Moderate	Moderate	Production Scheduling
Meta-Learning	High	Low	Low	High	Adaptive Dispatching Systems
Domain Adaptation via RL	High	Medium	Low to Moderate	High	Job-Shop Optimization in Smart Factories

2.3 Case-Based Reasoning and Meta-Learning for Adaptation

Meta-learning and case-based reasoning (CBR) are two different but complementary learning paradigms that enable adaptive decision-making in complex environments. CBR captures and stores historical problem-solution pairs (cases) and reuses them to solve new problems that are similar to the past instances. In production systems, this approach is especially helpful for dealing with routine problems in scheduling, layout planning, and inventory control, which repetition can cause problem patterns [18]. One of the most notable aspects of CBR is that it is very easy to interpret while also allowing for improvement from every decision episode through case library expansion.

Yet, CBR does encounter difficulties when operating under high variability conditions. As the number of stored cases grows, so does the computational cost of retrieval, along with the likelihood of achieving exact or approximate matches. Even more challenging, CBR systems have difficulty with new problem configurations that lie beyond the boundaries of their historical case space. This limits their use in cross-domain applications until sophisticated generalization or adaptation case mechanisms are employed [19].

Meta-learning takes care of these issues by equipping models with the ability to reason about the underlying structure of task families, thus enabling adaptation with few examples. In the case of few-shot learning, for example, a certain group of meta-learners is trained over several domains to minimize an outer-loop loss which diverges a model from overfitting. In the context of production networks, meta-learning enables systems to capture decision-making strategies such as workload distribution, buffer allocation, or task assignments in high-level concepts like policies. Such policies can be applied to certain domains with little adjustment required.

This advancement includes a applicational form of meta-learning (MAML) that is used for static scheduling problems where jobs and machines have certain attributes which change with time. Other neural studies have proposed the idea of encoding task descriptors into the corresponding neural policy networks, thus permitting the employment of common representations in multiple areas. For instance, some scientists claim that dispatching policies based on meta-learning and trained on synthetic job-shop data can transfer to real manufacturing data and lose less than 10% of their performance.

In relation to the current article, MML is a primary approach that enables transfer of decision making heuristics in and out of the domain AND area which defines a domain in ambiguous terms and does not allow a direct task assignment. Nevertheless, putting this into practice calls for the exact specification of meta features, multi-environment simulations, and metrics that combine evaluation of the iterations' performance on generalization with the assessment of its cost.

2.4 Gaps in Generalizability Across Heterogeneous Domains

There are many so-called "black holes" of bounded generalization, be it of any kind across different meta-boundaries, macro areas, or regions of the same meta domain. Many previous researches nad even practical approaches gap the expected efficiencies in obtaing stable generalization results across

different domains due to the existence of multiple gaps. Most of the existing literature emphasizes the intra variation within a single domain, like different types of tasks in the same plant, than the outer, inter domain, variations such as shift from batch to continuous systems or from electronics to foods.

The absence of standardization when it comes to domain representation is a primary reason for this boundary. Compared to NLP and computer vision fields, where representation of input such as word embeddings or pixel arrays are well-known, the industrial decision space is complex as it consists of a multitude of different types of unstructured data. This poses a challenge in developing universally applicable encoders or similarity metrics for aiding transfer decisions.

This issue is compounded by the lack of benchmark datasets and evaluation methods. Although there are simulation environments such as the Job-Shop Scheduling Problem (JSSP) instances or Taillard benchmarks, they usually do not have the correct degree of structural variability for testing cross-domain heuristic transfer. There is an urgent requirement for multi-domain simulation suites that enable the assessment of models by providing a wider range of production conditions including continuous process systems or high-mix, low-volume lines.

Moreover, numerous existing models fail to incorporate drift, which is the slow or sudden deviation from the system's behavior that was set during training owing to a machine state, supply, operator action, or product features. Systems that cannot monitor and adjust to drift usually deteriorate with time, even if they seem to do well initially once deployed. Hence, any plausible cross-domain heuristic framework needs to deal with drift detection and requires re-adaptation at the very least within its main design.

Finally, there is a lack of attention on cost-sensitive transfer which incorporates not only accuracy or throughput, but also the cost of implementing, maintaining, and adapting, the transferred heuristics. In practice, a heuristic with a weak performance margin that results in re-training, system reconfiguration, or provisioning a lot of manual supervision becomes useless. This highlights the need for a change in focus in how research is conducted from the emphasis on hit performance numbers to being cost-sensitive and operationally realistic.

3. Problem Formulation

3.1 Defining Domain Variability in Production Networks

Networks with a high degree of variability contain systems that differ not only in their operational parameters but also in their structural, behavioral, and time-based characteristics. Grasping the essence of variability present in production systems is profound, especially with regard to how decision heuristics like dispatching rules, buffer control tactics, and inventory policies operate across different domains. A domain, in this respect, encompasses a distinct fusion of production logic, set constraints, task flows, and the goals associated to a specific industrial environment.

Domain adaptation tends to be tackled in the literature by treating it as a problem of some (statistical) degree of similarity, concentrating on the distributions of the domain's inputs or outputs.

However, in production systems, there is also consideration variability in terms subjects of known process topology, resource heterogeneity, customer expectation, and the system feedback loop. Hence, constructing an understanding of formulating domain variability becomes a necessity of modeling the transferability of constructed heuristics.

To better describe the current problem, we capture the complexity by defining a domain variability space D containing multidimensional descriptors that correspond to the fundamental characteristics of production systems. Any domain $d \in D$ can be defined as a combination of n variability features:

$$d=\{v_1,v_2,v_3,...,v_n\}$$

where v_i is a particular variability dimension, for example, product mix, process topology, and machine capability distribution. The greater the dissimilarity between two domains d_i and d_j, the more complex the transfer of heuristics between dissimilar domains is.

The table illustrates the most important factors of production systems domain variability and heuristics transferability, and describes each factor's impact to the transfer of decision heuristics.

The variablility factors affecting construct operational behavior of system significantly and those that affect whether a decision heuristic can, or can be adapted at all, in another domain. For example, a reinforcement learning agent trained in a low feedback latency environment may become unstable in a domain that has a significantly delayed and noisy feedback.

One must rigorously measure the distance or likeness of domains along these variability axes to construct a strong cross-domain heuristic transfer model. This helps to intelligently reuse or adapt policies and aids in developing meta learners who possess internalized transferable knowledge across the variability space D.

Table 3: Domain Variability Dimensions in Production Networks.

Dimension	Definition	Impact on Heuristic Transfer
Product Mix Variability	Range and diversity of products manufactured simultaneously	Affects generalizability of dispatching and routing policies
Demand Volatility	Fluctuations in order quantities and frequencies over time	Requires adaptive planning strategies and dynamic buffers
Process Topology	Layout and flow structure of the production system	Alters applicability of learned task sequences and dependencies
Machine Capability Heterogeneity	Differences in speed, availability, and processing capabilities of resources	Influences feasibility of resource allocation strategies
Order Customization Rate	Degree to which orders are tailored to specific customer requirements	Limits reuse of one-size-fits-all policies
Constraint Tightness	Extent of hard vs. soft constraints on resources and operations	Changes prioritization rules and feasibility checks
Feedback Latency	Time delay between action and observable impact on the system	Delays reward propagation in RL-based systems
Scheduling Granularity	Resolution at which scheduling decisions are made (e.g., seconds vs. days)	Impacts precision and scope of transfer functions

3.2 Representation of Decision Heuristics

A decision heuristic involves the adoption of a formal policy π which defines a mapping of a state of a system $s \in S$ to an action $a \in A$ such that:

$$\pi: S \rightarrow A$$

A complex heuristic can be a custom procedure such as a logic rule (EDD or SPT), machine learning trained parameterized functions, reinforcement learning deep neural networks, or even an agent control module brought down to a symbolic decision tree.

Heuristic models should be chosen based on their complexity level and ability to be reused later on. Although they are easy to understand and apply, rule-based heuristics have low flexibility and application scope. On the opposite, parameterized models can allow formation of complex dependencies, but are challenging to engineer. Deep neural policies are currently the best option because they are straightforward to implement, but also difficult to explain and often lead to losing information when changing context.

Let us make the transfer heuristics more formal. Let us consider a source domain $d_s \in D$ with an existing policy π_s and a target domain $d_t \in D$. The goal is to create or modify a policy π_t to fit the target domain which can be expressed as follows:

$$\pi_t = \mathrm{T}(\pi_s, d_s, d_t)$$

Where T is a transfer or adaptation function which relies on the context of π_s and the domains. The success of heuristic transfer is determined by how accurate T is.

There are three general approaches to represent and modify heuristics:

1. Directly Reuse: Implement π_s on d_t without any modifications and it is only possible when $d_s \approx d_t$
2. Fine-Tuned Adaptation: Change some parameters of π_s with certain data from d_t.
3. Meta-Heuristic Abstraction: Construct a meta-policy such us π^* that can be created in other domains with a few changes.

This paper directs its attention to the third approach which we claim has the highest transferability, especially when the space of variability is large and retraining at the domain level is not feasible.

3.3 Transferability Metrics and Evaluation Objectives

Assessing the success of heuristic transfer involves looking at more than just the performance in the target domain. Standard metrics like throughput, makespan, and reward signal offer important

insights, but they do not account for the cost, robustness, and stability of transfer. In this regard, we identify four major metrics of transferability:

1. **Relative Performance Retention (RPR):** Estimates how much performance is maintained from the source domain in the target domain, and it is defined as:

$$RPR = \frac{P_t(\pi_s)}{P_t(\pi^*)}$$

where $P_t(\pi_s)$ is the performance of the heuristic in d_t, whereas, π^* is a heuristically trained for d_t.
2. **Adaptation Overhead (AO):** Estimates the time, data, or computational resources needed to transform π_s into a functional π_t. Better transferability is indicated by a lower AO number.
3. **Drift Stability Index (DSI):** Quantifies the robustness of the transferred heuristic against dynamic drift in d_t, which includes system shocks or any shifts in bottlenecks and arrival rates.
4. **Cross-Domain Generalization Score (CDGS):** It aggregates RPR and DSI with number of domains to assess the average generalization capacity of the heuristic across *n* target domains.

$$CDGS(\pi_s) = \frac{1}{n}\sum_{i=1}^{n}[\lambda_1 \cdot RPR_i + \lambda_2 \cdot DSI_i]$$

These exponent values assist in analyzing the transfer of design heuristics at varying levels of depth. A successful cross-domain heuristic will have a high RPR, low adaptation cost, ample stability with decreasing domains, and a strong CDGS with the entire system portfolio.

For the evaluation (to be shown in Section 6), we study these metrics in the context of comparing various approaches of heuristic transfer across five domain pairs with more variability like discrete versus continuous systems or high-mix against low-mix environments.

3.4 Scope and Constraints of Cross-Domain Analysis

The blend of definition bounds of decision heuristics' transferability has both delimitations, theoretical and practical, which need to be worked out within any meaningful analysis.

Firstly, domain non-overlap is a hard cap on policy generalization. Given that two domains do not share any concepts and operational relations like flow-shop versus batch-chemical systems, transferability is highly unlikely without deep decision logic. This is where embedding techniques and meta-learning become relevant.

Second, the mismatch in the reward signal can negatively affect the adaptation process. An heuristic optimized to minimize makespan in the source domain can severely underperform when the target domain emphasis cost, energy consumption or customer due dates. Objectives and functions must be aligned to reduce disjointive transfer or cross-referential semantic integration.

Third, diversity in the input space can limit the model's compatibility. For example, a policy based on machine utilization and backlog may not be compatible with a target domain that does not have these attributes or measures them in a different way. This gap can be closed by alignment, normalization of the input spaces or using learned embedding vectors.

Fourth, susceptibility to drift needs to be explicitly modeled. Production systems tend to change over time, meaning that the transferred heuristics will need to autonomously modify themselves or else they will become useless very quickly. To lessen this threat, the framework can integrate drift-detection and some form of online learning into the heuristic.

Lastly, system resources pose a significant challenge for most industry workloads. Scheduling in real-time, nodes for edge computing, and embedded systems have no, or very little, chance to afford high latency cycles for adjustments. The system's operational rhythm has to dictate what changes and what functions are used.

Our framework, as described in the following section, utilizes a combination of domain embeddings, cost-aware adaptation strategies, and resistance to drift within a meta-learning architecture. We aim to perform a cross-domain analysis that includes simulations and their real world counterparts, allowing the model to be both theoretically sound and practically tested.

4. Proposed Framework for Heuristic Transfer

4.1 Architecture of the Transferable Learning System

Building a complete learning system for cross-domain decision heuristic transfer is fundamentally challenging to do because transferable structure must be captured from the source domain while being able to transfer to a target domain with minimal computation or data. This proposed architecture integrates a multi-stage modular design that abstracts domain variability, learns generalizable decision-making strategies, and enables feedback-driven runtime adaptation as a way to solve this problem.

The proposed system architecture relies on five abstract components: (1) domain embedding characterizes the operational features of production environments; (2) heuristic policy embedding translates decisions made in a specific domain to policies to be used in a different domain; (3) meta-learner captures knowledge from the set of domains and returns in reusable form; (4) adaptation engine converts the policy from the meta-learner to a specific domain, and (5) reinforcement learns monitors streaming data to learn and change. Each component is built with the capability of interacting with all others, which would provide loose coupling to allow scalability and modular enhancements to be made easily.

The framework's foundation lies in meta learning, which means learning how to learn. It goes deep as it requires a system to not only recall specific decision rules, but memorize the structure of decision-making across different domains. This is achieved via episodic training on domain samples from a specific variability space (defined in section 3), where each episode is a unique set of constraints, objectives, and processes topologies.

Using meta learning, a shared structure across different domains is created by domain embedding, which allows the system to be aware of contextual features and makes the response domain-sensitive. Afterwards, the general approach is adapted to specific local conditions by the adaptation engine, whilst the performance is reinforced continuously in the target domain with the feedback loop. The table illustrates key components of the framework and the associated technologies.

Table 4: Core Components of the Transferable Heuristic Learning Framework

Component	Functionality	Key Technologies
Domain Embedding Module	Encodes domain-specific variability into a fixed-length vector representation	Autoencoders, Graph Embedding, Task Descriptors
Heuristic Abstraction Layer	Extracts transferable features from learned policies	Feature Extraction, Policy Embeddings
Meta-Learner	Trains across multiple domains to generalize decision principles	MAML, Reptile, Prototypical Networks
Adaptation Engine	Fine-tunes heuristics to specific target domains with low adaptation overhead	Gradient Updates, Attention Mechanisms
Reinforcement Feedback Loop	Provides real-time performance signals to guide ongoing policy refinement	Reward Modeling, Actor-Critic RL, Online Learning

4.2 Domain Embedding and Similarity Modeling

Transferring information between domains necessitates a simple yet complex requirement: quantifying their similarity or dissimilarity. This quantification is fundamental because it informs the system whether heuristics can be transferred and which dimensions need retuning. Therefore, for this purpose, the domain embedding module enclodes each production domain into a fixed-dimensional vector representation that captures its key variability dimensions (as discussed in Section 3.1).

These embeddings serve multiple purposes: (1) they act as context for meta-learner to differentiate the scope of the parameterized model that needs to be trained; (2) they can be used as indices for heuristics in case-based adaptation; and (3) they can be used as attention layer inputs in the adaptation engine to focus on pertinent domain features during the fine-tuning process.

To create embedding domains, three methods can be used:

- Autoencoders: A type of unsupervised neural networks that take as input domain descriptors, such as order patterns or machine graphs, compress them into a compact vector, and tries to reconstruct it with the least amount of error.
- Graph Neural Networks (GNNs): Used when the process topologies are modeled as directed acycle graphs (DAGs), enabling the combination of structural and flow information.
- Task Descriptors: Summary features that encapsulate operational characteristics of a task like number of product variants, average lead time variability, or constraint tightness index.

More precisely, we can define the embedding function as follows:

$$\phi : D \rightarrow \mathbb{R}^k$$

Where $d \in D$ to latent vector of dimension k. During Meta-training, domain ϕ embeddings are concatenated or used as conditions for policy parameters, so the model learns domain dependent behavioral modifications.

For measuring domain similarity, we use either cosine similarity or Mahalanobis distance in the embedding space, enabling clustering and heuristic transfer decisions to be made with a learned

geometric interpretability of domains' relationships. This structure-aware embedding is important in ensuring that decision heuristics learned in the system are not generalized beyond the region where they are applicable, hence deployed contexts.

4.3 Meta-Learner for Heuristic Abstraction

The meta-learner is at the center of the framework. It is in charge of formulating high-level decision-making strategies from multiple source domains and generalizes them for low-shot adaption to new domains. The meta-learner functions with the concept of episodic training, where each episode is defined as a combination of a domain and a task with a specific set of rewards, constraints, and dynamics.

We execute the Meta-Agnostic Model-Agnostic Meta-Learning MAML approach for a meta-reinforcement learning task, which focuses on discovering an optimal set of policy parameters that can be adjusted to a new target domain with a few gradient steps. The objective function for meta-training is written as follows:

$$\min_{\theta} \sum_{d_i \sim \mathcal{D}} \mathcal{L}_{d_i}(\theta - \alpha \nabla_{\theta} \mathcal{L}_{d_i}(\theta)))$$

This is where the θ set represents all parameters shared across domains and in this problem, $\mathcal{L}_{d_i}$ is the loss in domain d_i and α is the inner-loop learning rate. With this formulation, the model is ensured to not only learn a domain specific optimal solution, but rather the optimal solution that will allow the model to get to the domain specific optimal solutions provided a good starting point is given.

We try out Prototypical Networks and Reptile as other alternatives of meta-learning strategies. In certain scenarios, approximaid divergences offer reduced calculative load and improved empirical convergence. Aside from them, Prototypical Networks are quite effective in contexts where decision heuristics are captured as discrete or symbolic templates or rules.

Along with these, the features of a specific domain together with the system state form the input which can be used for the meta-learner, hence enabling the model to contextually adapt the decision making strategies. The output can be in the form of several possible sets direct action values (e.g., dispatching priorities); (2) abstract downstream interpreted policy vectors, or (3) rules instantiated and expressed in for interpretable formats.

By cycling through highly varied domain-task episodes, the meta-learner skims the surface across multiple areas to form an outline for a task-generalizable policy manifold, capturing all the essential pieces required to perform a set of tasks across domains. This abstraction facilitates the implementation of policies in unfamiliar contexts where, problematically, the training data is scant or even entirely absent.

4.4 Reinforcement Feedback Loop for Adaptive Tuning

Even though the meta-learner sets a weak heuristic initialization, the real-world use case must default to continually evolving decision heuristics to local dynamics, shifts in the input distribution, or a drift

in performance over time. In order to accommodate this, we include a feedback reinforcement loop within the line of the pipeline that allows for the real time tuning of decision strategies based on performance indicators.

As with any closed feedback loop system, this specific one will iterate through the following steps: as soon as the target domain is deployed, the system starts with the meta-learned heuristic, and while the system is on, it collects state-action-reward trajectories in an unsupervised scheme. After this, these trajectories are run through a set process that allows them to compute temporal-difference errors, policy gradients, or any other signal able to be learned, which will be used to incrementally update the policy that has already been deployed.

We utilize a mix of actor-critic reinforcement learning alongside some of the policy gradient methods dependent on the nature of the domain's reward and available computational power. The loop for adaptation has the ability to work all the time online or with set periodic intervals making it possible to control the needed delay and the stability limits. This infers the advanced construction of the targeted reward function to encompass operational objectives like as throughput, tardiness, inventory levels, or machine utilization. In order to prevent catastrophic forgetting, we employ trust region optimizations such as TRPO or PPO together with experience replay buffers to constrain updates within a safe performance envelope.

The meta-learner and domain embedding augmenting techniques enable the system to self-correct by invoking a re-initialization from the meta- learner or selectively incorporating new structural insights. Performance degradation or structural drift within the environment can be independently diagnosed by the system through the policy introspection layer. The implementation of learning as a deployment construct, instead of a single static task, means that systems can be designed for stronger adaptability, flexibility, and autonomy. This flexes the boundary in dynamic policy deployment and construction strategy. Such adaptation allows advanced production systems to adapt, survive, and thrive in rapidly changing environments.

5. Experimental Setup and Domain Definitions

5.1 Source and Target Domains

To empirically test the portability of decision heuristics between distantly spaced production environments, three pairs of source-target domains were identified. These domains were crafted to exhibit notable operational, structural, and temporal differences. The aim was to find out the degree to which heuristic learning in one context was applicable to another context that had different product flow processes, schedule constraints, and feedback mechanisms. Selected pairs include the moves from automotive assembly to electronics manufacturing, semiconductor fabrication to machining of aerospace components, and food packaging to bottling of pharmaceuticals.

The automotive assembly to the electronics manufacturing transition illustrates the movement from a sequential, moderately schedule-driven environment to one with high variability product mix, Surface Mount Technology (SMT) flows, and heavy utilization of machines. In the semiconductor

Table 5: Source and Target Domain Pairs with Key Characteristics.

Domain Pair	Source Domain Characteristics	Target Domain Characteristics	Domain Variability Index (0–1)	Similarity Score (0–1)
Automotive Assembly → Electronics Manufacturing	Sequential workflow, moderate customization, low downtime tolerance	Highly variable product mix, SMT-based flow, high equipment utilization	0.68	0.42
Semiconductor Fab → Aerospace Machining	Batch processing, long processing times, cleanroom constraints	Precision-focused, component-level scheduling, high rework sensitivity	0.77	0.35
Food Packaging → Pharmaceutical Bottling	High speed, low customization, FIFO dominant	Regulatory constraints, batch records, process validation cycles	0.52	0.51

to aerospace transition, the domain shifts from cleanroom batch processing environments with long cycle times to high precision, component machining-level operations where sensitivity to rework and traceability of components are important. Finally, the food packaging to pharmaceutical bottling transfer tests a case with comparable batch processing systems but differing in the nature of regulation, process validation, and data traceability requirements.

Two indices were crafted to evaluate and score the domains. Domain Variability Index (DVI) measures the degree of structural and behavioral differences among the domains within the normalized 0-1 scale. Similarity Score (SS) computes the geometric proximity of domain embeddings on bits of multi-ordinal task descriptors. In sum, these indices are useful to estimate the level of effort required to transfer heuristics between a particular set of domain pairs. The table below illustrates these pairings and some of their defining attributes and quantitative measures.

The selected domain pairs were thought to create a progressively more difficult task of heuristic transfer starting from moderate (food to pharma) to high (semiconductor to aerospace), hence, contributing to a more empirically grounded validation of the proposed framework.

5.2 Heuristic Types

The spectrum of strategies integrated within Industrial system operating strategies was used to evaluate the three categories of decision heuristics deployed in the experiments. The first category contained rule-based such as earliest due date (EDD), shortest processing time (SPT), and first-in-first-out (FIFO) dispatching rules. They are operative and efficient but static and optimized for specific domains, thus, being mostly fixed on specific interpretations.

The second group had RL-based heuristics, in particular source domain trained deep Q-networks (DQN) and actor-critic methods. The deep heuristics include RL methods that adapt to environmental feedback and can capture complex dependencies, but are often expensive to retrain or fine-tune in new environments. The third category involved hybrid heuristics that used

symbolic rules with neural function approximators or policy embedding modules. With these strategies, the strengths of interpretability of rule-based logic and the flexibility of machine learning were combined.

In each simulation run, the heuristics were initially trained or calibrated in the source domain. For transfer experiments, the pre-trained models or rule sets were transferred into the target domain without modification, so their baseline performance could be recorded. Later, in a second phase, these same heuristics had their model parameters changed by meta-learning and reinforcement feedback from Section 4. The amount of performance improvement against adaptation cost was tracked to evaluate the efficacy of cross-domain transfer.

5.3 Data Sources, Simulation Tools, and Domain Variability Scenarios

An AnyLogic and Simio combination was chosen to develop the hybrid discrete event agent-based simulation environments for the visual validation and control of behavioral emulation. Furthermore, reinforcement learning agents were trained and deployed through the use of OpenAI Gym compatible custom built Python environments with implemented TensorFlow and PyTorch libraries for policy feature estimation. These environments provided the needed autonomy for realistic reproduction of domain-specific complexities in regards to control of job arrival patterns, resource availability, machine downtimes, and feedback delay times, which facilitated the accurate simulation of operational dynamics of each domain.

For parameterization of the simulation models, historical data was collected from three publicly available manufacturing data sources alongside expert calibrated synthetic distributions that matched industrial benchmarks. These included Taillard and Demirkol instances, as well as the realistic job shop scheduling dataset offered by the Massachusetts Institute of Technology (MIT). The domain variability scenarios were changes in the degree of customization orders, demand volatility, machine capability distributions, and the granularity of scheduling orders.

To ensure convergence of performance metrics, five replicates were executed for every domain pair to accommodate stochastic variability. Each simulation was completed over a span of 10,000 virtual time units. This meant that in total, over 450,000 decision episodes and 4.5 million state transitions across domains were generated in the experiment.

5.4 Performance Metrics: Throughput, Makespan, Adaptation Cost

In order to assess the quality of heuristic transfer, the following metrics were included: throughput, makespan, retention, and adaptation cost. The definition of throughput was the number of jobs finished in a given time period. Makespan represented the total time taken to complete a batch of jobs. Adaptation cost was the time (in seconds) to adjust the heuristic in the target domain. Performance retention was the ratio of the performance of the heuristic in target domain versus a locally trained policy.



Figure 1: Performance Retention vs. Domain Variability.



Figure 2: Adaptation Cost Across Domain Pairs.

The relationship between domain granularity and performance retention is illustrated in the first graph below. You can see the retention value attained as variability increases (x-axis) and the ability of a heuristic to maintain source domain performance decreases (y-axis). These observations confirm the hypothesis that transferability declines with structural dissimilarity.

In the second figure, we focus on adaptation cost and highlight the time burden associated with adapting heuristics in more complex or dissimilar domains. It is evident from the graph that, filled with notable costs, these policies are bound to deeper policy change due to differing reward functions, task interdependencies, and feedback granularity that differentiates aerospace from semiconductor.

The aforementioned metrics, when combined with domain embeddings and drift measurements, form a comprehensve set capturing the transferability of different systems. Retention of performance and adaptation cost, in particular, are supportive of operational planning since they define the efficiency of reusing an existing heuristic versus retraining afresh.

A performance degradation measure over time in the absence of overt perturbations allowed for the calculation of the drift-resilience index. Even though not presented here, the metric computed reveals the hybrid heuristics incorporating reinforcement feedback loops are much more stable in drift-prone environments than purely rule-based models and RL-only models.

In order to confirm the findings, heuristic type, domain pair, and adaptation strategy performance were analyzed with ANOVA and Tukey's HSD test. Differences between adapted and non adapted heuristic implementation were found to be significant ($p < 0.01$) across the measure of throughput and makespan in the case of high variability domain pairs.

6. Results and Performance Evaluation

6.1 Intra-Domain vs. Cross-Domain Performance

The primary analytical axis revolves around the initial performance of the decision heuristics within their source domains and how they were subsequently used in target domains without any modifications. This internal domain comparison versus cross domain comparison provides the novel approach in metric evaluation for transfer success and showcases the loss patterns that require adaptive decisions. The heuristics trained and validated in their source domains of Automotive Assembly, Semiconductor Fabrication, and Food Packaging were shown to perform efficiently throughout the domain in standard measures of efficiency, such as makespan and throughput. When these were inserted into target domains of Electronics Manufacturing, Aerospace Machining, and Pharmaceutical Bottling without context retraining or tuning, there was a universal performance decline across all heuristic types. The performance drop was especially large for RL-based heuristics which, in spite of their complexity, turned out to be more brittle than the rule-based or hybrid models regarding robustness to out-of-distribution applications.

In their respective domains, the cross-domain makespan values are lower than the intra-domain values, reflecting the fact that domain differences in structure and behavior tend to reduce decision-making efficiency. For example, in the transition from Semiconductor to Aerospace the makespan increased from 1340 to 1685 units, while in the Automotive to Electronics transition the figure jumped from 820 to 975 units. The Food to Pharma scenario had a smaller increase from 510 to 615 units. As expressed in the performance table, the degree of this deterioration correlates with the domain variability index. The greater the difference between the source and target domains, the

Table 6: Heuristic Performance Comparison Across Domain Pairs.

Domain Pair	Heuristic Type	Intra-Domain Makespan (units)	Cross-Domain Makespan (Before Adaptation)	Cross-Domain Makespan (After Adaptation)	Performance Retention (%)	Adaptation Time (seconds)
Automotive Assembly → Electronics Manufacturing	Rule-Based	820	975	845	86.1	120
Semiconductor Fab → Aerospace Machining	RL-Based	1340	1685	1405	80.2	180
Food Packaging → Pharmaceutical Bottling	Hybrid	510	615	525	97.0	95

greater the performance drop which validates the theory that domain structure is essential to heuristic portability.

The effect of adaptation was equally impactful. When the heuristics in question were target modified through use of the reinforcement feedback loop and were placed into a context via domain embeddings, their performance nearly aligned with the intra domain baseline. Post adaptation, the Automotive to Electronics scenario saw makespan improve to 845 units which is a 13% improvement from the unadapted state. The Semiconductor to Aerospace transition also improved from 1685 to 1405 units, whilst the Food to Pharma scenario almost reached the intra domain baseline at 525 units. These improvements support the fundamental architecture of the meta-learning adaptation engine and its capability to offset domain induced deterioration.

6.2 Generalization Accuracy and Stability Under Variability

In addition to the fundamental performance metrics, it is equally important to analyze the degree to which heuristics fail in generalization across varies levels of structural and behavioral complexity in the target domains. The second set of analyses measured generalization accuracy using the Performance Retention metric, which is defined as the proportion of performance in the target domain relative to the source domain after adaptation divided by the domain's depth. As can be seen on Figure 4, performance retention is not constant across domain pairs. It was maximal in the Food-to-Pharma transfer at 97%, and minimal in the Semiconductor-to- Aersospace transfer at 80.2%. This variance corresponds to the calculated Domain Variability Index from Section 5.1. This supports the claim made that generalization accuracy has a negative correlation with the dissimilarity between the domains in question.



Figure 3: Makespan Comparison Before vs. After Adaptation.



Figure 4: Cross-Domain Performance Retention.

Particularly the case of hybrid heuristics that combine symbolic logic with policy networks was found to have an edge as their accuracy was higher in medium-to-high variable environments. These heuristics appeared to have less overfitting to domain specific details without loosing too much accuracy, which implies that these structural regularization and interpretability mechanisms enhance transfer robustness. In contrast, RL-only policies were less stable during high drift episodes and needed more tuning.



Figure 5: Heuristic Adaptation Cost.

The overall improvement, in this case the makespan, is provided in Figure 3. The reduction in makespan post fine-tuning is most prominent in the Semiconductor-to-Aerospace pair, which illustrates the effectiveness of the adaptation engine in makespan recovery. In the meantime, Figure 5 captures the adaptation cost in seconds depicted in each domain pair. The adaptation cost, although considerable, is far less than the full retraining cost of a heuristic from scratch. For example, the RL-based heuristic full retrain in Aerospace domain is greater than 1400 seconds but retuning the transferred policy took a mere 180 seconds while outperforming. This finding clearly shows the value heuristic transfer brings when deployed in real-world industrial settings where there is limited time and computational budgets for full model redevelopment.

6.3 Heuristic Drift and Re-adaptation Over Time

As a consequence of changing workload, status of the machine, and the process parameters, the production environment in real life is by default and naturally not so static, leading to a drift from optimal decision behavior. Operational sustainability in the long run hinges on how well a given heuristic can either maintain effectiveness or re-adapt efficiently. The focus of the third analysis was on stability measurement under drift with a 100-time step simulation period with a gradual increase in variability associated with the rates of job arrivals, distribution of processing times, and availability of machines.

Figure 6 illustrates the percentage of performance preservation over time for the three domain pairs. In the Food-to-Pharma scenario, the hybrid heuristic exhibited the highest stability, with performance retention decreasing from 98 percent to 88 percent in a time frame of 100 time units. In the Semiconductor-to-Aerospace scenario, the RL-based policy suffered the most performance



Figure 6: Stability of Heuristics Over Time Under Drift.

loss, declining from 95 percent to 67 percent due to high responsiveness to reward noise and feedback delay. The Automotive-to-Electronics transition exhibited moderate performance loss, gradually declining from 96 percent to 78 percent.

These findings underscore the trade-offs between the heuristic's complexity and the system's ability to resist drift. While and rule-based heuristics are quite stable, they do not adapt to drift unless there is online tuning. RL-based heuristics are more flexible, but they are highly susceptible to catastrophic forgetting without replay buffers and meta-stabilizers. Hybrid strategies are a compromise as they support flexibility while retaining modularity or interpretability.

To evaluate the efficiency of re-adaptation, the feedback loop of the system was re-engaged after every twenty five time units. It was the case, for the most part, that it was possible to restore performance within three to five update cycles, which confirms the effectiveness of incremental learning. This observation relates to the goal of the framework design which is continuous evolution of the heuristic enabling the device to deploy as opposed to being treated as a completed operation but as initiation of an endless learning loop.

6.4 Statistical Significance and Visual Performance Insights

The fourth dimension of the analysis was dedicated to the statistical validation and interpretation of heuristics' performance in different domains visually. To test the existence of significant difference across heuristic types, domain pairs, and adaptation states, a one-way ANOVA was calculated on makespan and throughput measures. The p-values for both metrics were below .01 for all domain pairs, which implies that the performance differences are indeed real and not due to random noise or perturbation simulation.

Use of Tukey's HSD test in post-hoc analysis showed that hybrid heuristics outperformed rule-based models and RL-only models in cross-domain retention and stability. Specifically, the hybrid model's outstanding performance stemmed from its ability to use domain embeddings for modulating policy. From visual examination of Figure 4 and Figure 5 it can also be reinforced that hybrid strategies have high performance retention and low adaptation cost.

Graphs provide additional support to the claims made previously, especially with respect to the proportions that adaptation mechanisms can lower makespan. Figure 6 can also be considered a strong evidential source, especially in relation to heuristic stability under drift, as it plots both performance decay and the speed of that decay. These images are useful in the context of industrial decision making where stakeholders may be more concerned with how inefficient strategies need to be to achieve the desired performance.

Another critical finding was noted when reviewing the variance of performance metrics pre- and post-adaptation. Average variation in makespan for the five runs per domain pair was observed to have reduced by approximately 37% post adaption, signifying an increase in robustness and repeatability. Such consistency is vital within industrial environments where the reliability of decision behavior is critical given its impact on supply chains and customer satisfaction.

7. Discussion

7.1 Key Takeaways on Transferable Decision-Making

The experimental analysis of high-variability production networks has presented impressive findings concerning the nature, applicability, and effectiveness of transferring decision heuristic learning over structurally different domains. Firstly, it is important to note that cross-domain heuristic transfer is possible and with contextual adjustment, can achieve resultados not too distant from those obtained with local models. This takes aim at the 'common wisdom' that decision agents need to undergo full retraining whenever there are significant changes in the environments. The transfer and reactivation of dependent decision making suggest a high level of embedded structural invariance of decision logic to be used in automotive assembly, electronics manufacturing, food packaging, and even pharmaceutical bottling.

What is clear is that the capability of achieving transferability greatly depends on whether the framework can condense domain-specific features into high-level abstractions that can control the modulation of heuristic activity. The boundaries defined by domain embeddings and meta-learned initialization points are what enabled effective generalization across different topologies and workflows. In particular, hybrid heuristics demonstrated exceptional generalization performance with interpretable decision-making logic, which is notably advantageous in industrial deployment where human-in-the-loop supervision is necessary.

The durability of these adapted heuristics under drift, which was earlier discussed in Figure 6 of Section 6 and reviewed within this section, illustrates that transfer-capable systems are not efficient

Table 7: Trade-offs Between Transfer and Retraining of Heuristics.

Evaluation Metric	Transfer (Adapted Heuristics)	Full Retraining	Operational Implication
Adaptation Time	Low (~100–200s)	High (~1000–1400s)	Faster deployment in production lines
Computation Cost (FLOPs)	Moderate	Very High	More scalable to compute-constrained edge settings
Initial Performance Drop	Medium	None	May affect short-term throughput
Final Performance Accuracy	High	High	Comparable long-term outcomes
Flexibility to Drift	High (via RL loop)	Medium	More robust to real-time variation
Interpretability	Medium	Low (if RL-based)	Easier handoff in human-AI systems
Training Data Requirement	Low	High	Enables lightweight onboarding in new domains



Figure 7: Adaptation Time vs. Final Accuracy.

only, they are robust. Constant policy refinement through reinforcement feedback was sufficient for the heuristics to adapt and contend with latent boundary shifts and workflow disruptions, which makes these heuristics suitable for real-time production settings that change due to internal and external causes. These findings confirm the employment of sophisticated multi-agent systems for the simulation of industrial cognition and endorse an old proposition in the adaptive system theory which states that modular learning architectures grant the possibility of general intelligence within a set of diverse and constrained task environments.

7.2 Trade-offs in Transfer vs. Retraining

The second central element corresponds to the operational and computational trade-off between the transfer of a learned heuristic and the retraining of a new heuristic, which was learned from the target domain. Both extremes are different not only in structural design, but also in the deployment, cost, and agility aspects.

The strategy of transfer has a clear advantage in terms of time and computational savings, as shown in the table above. Although performance dips after a transfer, the necessary time and cost to recover that performance is far more economical than full retraining, which is much more expensive. These benefits are further depicted in Figure 7.

In this figure, the blue bars illustrate the much lower adaptation time for the transferred heuristics, while the green line indicates that the accuracy achieved is comparable for both the transfer and retraining. This elucidates the point that although retraining starts from a baseline, the stability of the baseline is higher, the convergence speed of transfer strategies is much faster, and is resource-saving.

The choice for one strategy or the other is a function of operational needs. For rapidly-changing situations or constrained setups like edge computing systems, the transfer strategy is a more useful approach. However, for safety relevant situations with hard guarantees and regulatory scrutiny, retraining may be preferred even though it incurs an overhead. The important point is that transfer learning, even in these cases, can be used as a bootstrapping strategy to speed up early learning and minimize system downtime.

7.3 Organizational and Operational Implications

These results bear implications beyond the technical issues at hand and touch on strategic choices within contemporary manufacturing and supply chain processes. The cross-portability of heuristics across production lines, geographic subdivisions, or corporate branches enhances operational flexibility. There is considerable competitive advantage in a time characterized by increased demand volatility and decreasing product lifecycle due to the ability to reuse as opposed to reconstruct decision intelligence.

With respect to the matrix, the ability to use decision systems transferably lowers the dependency on domain-specific knowledge for every fresh deployment. Enterprises can now afford to delegate decision-making authority without losing control to the extent that operational performance gets compromised by the abstraction of operational logic into modular flexible policies. This helps support emerging models of intelligent distributed operations wherein local units can autonomously carry out their functions while leveraging globally established good practices.

This shift also has implications for talent strategy and training. Rather than expecting each plant or designated operating team to create its own unique assortment of scheduling logic or optimization routines, an organization can school, capture, and theorize instruction for widespread use with minimal change. Horizontal integration of sites could lead to quicker learning of new sites, shortened training periods, and greater consistency in the decision-making processes of various teams.

The above-mentioned points are further reinforced by Transfer Adapted Heuristics outperforming Fully Retrained Models in maintaining stability under simulated drift which is illustrated in Figure 8.

In the figure titled "Drift Resilience Over Time," it's clear that during a simulation period of 100 intervals, the performance retention of transfer adapted heuristics remained continuously superior to that of Extensively retrained models. Fully retrained heuristics have an initially strong performance, but decay more quickly in unstable conditions due to overfitting to surrounding conditions. Fully transfer models however, do maintain robustness under consistent system perturbation because they are able to leverage structural embeddings and adaptive feedback.

These findings point out that, unlike previously considered, transfer systems not only allow for efficient work, but also aid in resilience. When considering how volatile the external operating environment is, whether by geopolitical, supply chain, or even climate changes, the ability to maintain stable performance while drifting away from the system becomes as vital as the original performance accuracy itself.

7.4 Limitations and Robustness Challenges

While this study is promising, there remain several limitations that must be addressed. Firstly, domain variability was captured in a wide array of structural and behavioral dimensions, but there still remains significant gaps in the attempts to simulate the complex real-life systems of industries. Further research should look into dimensions of human-machine collaboration, maintenance uncertainty, and multi-enterprise coordination which would enable the results of the findings be used more broadly.



Figure 8: Drift Resilience Over Time.

Alongside, the meta-learning algorithms (MAML and Reptile) used are hyperparameter sensitive and unless restructured, they do not scale well to hundreds of domains. More work remains to create hierarchical transormer meta-learners capable of efficiently compressing and recalling multi-domain policies. Likewise, domain embeddings in this architecture were either handcrafted or trained with weakly shallow encoders. In reality, more elaborate task descriptions alongside self-supervised domain adaptation would enhance the embedding power and mitigate embedding collapse, in which two domains are so superficially similar, yet functionally different, that they become a single domain.

A third limitation is the balance between generalization and interpretability. Once policies become more relaxed and driven through data, the internal workings become hard to explain to a user or a regulatory body. Although hybrid heuristics help with maintaining this balance, there is still a lack of explainable reinforcement learning (XRL) and interpretable optimization systems in which the decision makers can analyze the AI-driven actions and validate them.

8. Conclusion and Future Directions

This research developed a new model aimed at the transfer of learned heuristics for decision-making in systems with differing degrees of structural and behavioral complexity. The approach presented is based on combinations of domain embeddings, meta-learning, reinforcement feedback loops, and hybrid decision architectures, which enabled strong adaptation to new domains after limited retraining. A large number of simulations were run using pairs of domains representative of various industries like the automobile and electronics industries, as well as the semiconductor and aerospace industries. The results demonstrated that the performance of the heuristic transfer was preserved at a high level while needing much less time and computation costs to adapt these systems than complete retraining. The results clarified also the dominance of hybrid heuristics relative to their accuracy, drift tolerance, and interpretability under real world variability and system noise in latent perturbations.

Aside from the technical validation, the results have have their contributions both on a deeper level and in practicality. From a theoretical perspective, the research deepens the scope of transfer learning in AI within industries by actualizing intricate meta-learning systems in high-variability manufacturing. It contributes to the literature by defining the interplay between domain closeness, heuristic generalization, and drift-resilience which provides a guide for scalable decision making in situations fraught with uncertainties. From practical perspective, the study enables corporations to harness reusable intelligence in a putative fashion deployed across a fragmented operations, which diminishes reliance on domain-centric modeling and enhances the pace of digital transformation. The transferability and adaptation of heuristics at speed is possible, which creates possibilities for managing production agility, particularly in resource, regulatory, or rapid fluctuation constrained settings.

Looking further, the study opens up possibilities for advanced real time adaptation such as in the context of Industry 5.0, where human-machine collaboration and cognitive automation will require even more sophisticated and explainable decision making systems. The incorporation of decentralized multi-agent systems for coordination, human supervisory control for safe intervention, and

zero- shot transfer learning for data scarce regions offer great opportunities. Also, future work should include federated learning for boundary- crossing privacy-sensitive data transfer, and flexible production and task allocation or so-called dynamic task graphs enable a never-ending modification of production objectives. All-in-all, this study leads toward efficient intelligent manufacturing systems and offers a greater understanding of them in regard to their resilience, adaptability, and contextual awareness which are the defining traits of the impending industrial artificial intelligence systems.

References

1. Leng, Jiewu, et al. "Digital twin-driven manufacturing cyber-physical system for parallel controlling of smart workshop." *Journal of ambient intelligence and humanized computing* 10 (2019): 1155–1166.
2. Wang, Lihui, Martin Törngren, and Mauro Onori. "Current status and advancement of cyber-physical systems in manufacturing." *Journal of manufacturing systems* 37 (2015): 517–527.
3. Lu, Yang. "Artificial intelligence: a survey on evolution, models, applications and future trends." *Journal of Management Analytics* 6.1 (2019): 1–29.
4. Bousdekis, Alexandros, et al. "A review of data-driven decision-making methods for industry 4.0 maintenance applications." *Electronics* 10.7 (2021): 828.
5. Dolgui, Alexandre, and Jean-Marie Proth. *Supply chain engineering: useful methods and techniques*. Vol. 539. London: Springer, 2010.
6. Zhong, Ray Y., et al. "Intelligent manufacturing in the context of industry 4.0: a review." *Engineering* 3.5 (2017): 616–630.
7. Bousdekis, Alexandros, et al. "A review of data-driven decision-making methods for industry 4.0 maintenance applications." *Electronics* 10.7 (2021): 828.
8. Zhou, Longfei, Lin Zhang, and Berthold KP Horn. "Deep reinforcement learning-based dynamic scheduling in smart manufacturing." *Procedia Cirp* 93 (2020): 383–388.
9. Guo, Shu, et al. "Inventory management in mass customization operations: A review." *IEEE Transactions on Engineering Management* 66.3 (2018): 412–428.
10. Niu, Shuteng, et al. "A decade survey of transfer learning (2010–2020)." *IEEE Transactions on Artificial Intelligence* 1.2 (2021): 151–166.
11. Li, Shufei, and Pai Zheng. "Transfer learning for smart manufacturing: A stepwise survey." *IFAC-PapersOnLine* 53.5 (2020): 37–42.
12. Comas Herrera, Pau. *Transferability of deep learning models in industrial control systems*. MS thesis. Universitat Politècnica de Catalunya, 2024.
13. Mönch, Lars, John W. Fowler, and Scott J. Mason. *Production planning and control for semiconductor wafer fabrication facilities: modeling, analysis, and systems*. Vol. 52. Springer Science & Business Media, 2012.
14. Fan, Hua-Li, et al. "Survey of the selection and evaluation for dispatching rules in dynamic job shop scheduling problem." *2015 Chinese Automation Congress (CAC)*. IEEE, 2015.
15. Katoozian, Hoora, and Masoumeh Kazemi Zanjani. "Supply network design for mass personalization in Industry 4.0 era." *International Journal of Production Economics* 244 (2022): 108349.
16. Li, Shufei, and Pai Zheng. "Transfer learning for smart manufacturing: A stepwise survey." *IFAC-PapersOnLine* 53.5 (2020): 37–42.
17. Liu, Yi, et al. "Domain adaptation transfer learning soft sensor for product quality prediction." *Chemometrics and Intelligent Laboratory Systems* 192 (2019): 103813.
18. Richter, Michael M., and Rosina O. Weber. *Case-based reasoning*. Springer-Verlag Berlin An, 2016.
19. Müller, Gilbert, and Ralph Bergmann. "Workflow streams: a means for compositional adaptation in process-oriented CBR." *International Conference on Case-Based Reasoning*. Cham: Springer International Publishing, 2014.